

Garant
Boring bar steel, left-hand, Shank Ø / insert size: 40/11 mm

Order data

Order number	260343 40/11
GTIN	4045197656025
Item class	21T

Description

Boring bar steel 40/11 mm Shank Ø D_s : 40 mm
 ISO code toolholder: A40T SDUCR/L11
 Setting angle κ : 93 degrees
 suitable indexable insert: DC.. 11T3..
 Minimum pre-drill Ø D_{min} : 49 mm
 Centre offset L_3 : 27 mm

Technical description

Minimum pre-drill Ø D_{min}	49 mm
suitable indexable insert	DC.. 11T3..
Shim	269005 3
Insert size	11 mm
Shim screw	269013 4
Pack of insert screws	269028 24
ISO code toolholder	A40T SDUCR/L11
Centre offset L_3	27 mm
Overall length L	300 mm
Clamping height L_2	39 mm
Setting angle κ	93 degrees
Shank Ø D_s	40 mm

Application type	left-hand
Boring depth up to	3×D
Standard	DIN 8024
Through-coolant	yes
Type of product	Boring bar

Accessories

PrecisionBit for Torx®, shank E 6.3 Torx® profile TX15	674248 TX15
Set of insert screws Type 24	269028 24
Set of insert screws Type 8	269028 8
Set of insert screws 10 pieces	269468
Torque screwdriver with scale, to take interchangeable blades maximum torque 500 cNm	659906 500
Shim	269010
Set of insert screws 10 pieces	269414
Shim screw Type 4	269013 4
Shim Type 3	269005 3
Shim screw	269202