

Garant
Boring bar, steel, right-hand, Shank \varnothing / insert size: 12/07 mm

Order data

Order number	260344 12/07
GTIN	4045197877932
Item class	21T

Description

Boring bar, steel 12/07 mm Shank \varnothing D_s: 12 mm
 ISO code toolholder: A12L SDXCR/L07
 Setting angle κ : 93 degrees
 suitable indexable insert: DC.. 0702..
 Minimum pre-drill \varnothing D_{min}: 17 mm
 Centre offset L₃: 9 mm

Technical description

suitable indexable insert	DC.. 0702..
Setting angle κ	93 degrees
Head length L ₁	25 mm
Clamping height L ₂	11 mm
ISO code toolholder	A12L SDXCR/L07
Pack of insert screws	269028 7
Centre offset L ₃	9 mm
Insert size	7 mm
Overall length L	140 mm
Minimum pre-drill \varnothing D _{min}	17 mm
Usable depth T	4.3 mm
Shank \varnothing D _s	12 mm

Application type	right-hand
Boring depth up to	3×D
Standard	DIN 8024
Through-coolant	yes
Type of product	Boring bar

Accessories

PrecisionBit for Torx®, shank E 6.3 Torx® profile TX8	674248 TX8
Torque screwdriver with scale, to take interchangeable blades maximum torque 500 cNm	659906 500
Set of insert screws 10 pieces	269413
Set of insert screws Type 7	269028 7