

Garant

Boring bar, steel, right-hand, Shank \varnothing / insert size: 16/07 mm



Order data

Order number	260344 16/07
GTIN	4045197877949
Item class	21T

Description

Boring bar, steel 16/07 mm Shank \varnothing D_s: 16 mm
 ISO code toolholder: A16Q SDXCR/L07
 Setting angle κ : 93 degrees
 suitable indexable insert: DC.. 0702..
 Minimum pre-drill \varnothing D_{min}: 21 mm
 Centre offset L₃: 11 mm

Technical description

suitable indexable insert	DC.. 0702..
Overall length L	180 mm
Centre offset L ₃	11 mm
Setting angle κ	93 degrees
Pack of insert screws	269028 7
Head length L ₁	33 mm
Insert size	7 mm
Minimum pre-drill \varnothing D _{min}	21 mm
ISO code toolholder	A16Q SDXCR/L07
Clamping height L ₂	15 mm
Usable depth T	4.3 mm
Shank \varnothing D _s	16 mm

Application type	right-hand
Boring depth up to	3×D
Standard	DIN 8024
Through-coolant	yes
Type of product	Boring bar

Accessories

Set of insert screws Type 7	269028 7
Set of insert screws 10 pieces	269413
PrecisionBit for Torx®, shank E 6.3 Torx® profile TX8	674248 TX8
Torque screwdriver with scale, to take interchangeable blades maximum torque 500 cNm	659906 500