

**Garant**
**Boring bar, steel, left-hand, Shank Ø / insert size: 12/07 mm**

**Order data**

Order number	260345 12/07
GTIN	4045197877970
Item class	21T

**Description**

Boring bar, steel 12/07 mm Shank Ø  $D_s$ : 12 mm  
 ISO code toolholder: A12L SDXCR/L07  
 Setting angle  $\kappa$ : 93 degrees  
 suitable indexable insert: DC.. 0702..  
 Minimum pre-drill Ø  $D_{min}$ : 17 mm  
 Centre offset  $L_3$ : 9 mm

**Technical description**

Minimum pre-drill Ø $D_{min}$	17 mm
suitable indexable insert	DC.. 0702..
Centre offset $L_3$	9 mm
Pack of insert screws	269028 7
Head length $L_1$	25 mm
Setting angle $\kappa$	93 degrees
Insert size	7 mm
Overall length L	140 mm
ISO code toolholder	A12L SDXCR/L07
Clamping height $L_2$	11 mm
Usable depth T	4.3 mm
Shank Ø $D_s$	12 mm

Application type	left-hand
Boring depth up to	3×D
Standard	DIN 8024
Through-coolant	yes
Type of product	Boring bar

---

## Accessories

PrecisionBit for Torx®, shank E 6.3 Torx® profile TX8	674248 TX8
Torque screwdriver with scale, to take interchangeable blades maximum torque 500 cNm	659906 500
Set of insert screws Type 7	269028 7
Set of insert screws 10 pieces	269413