

**Garant**
**Boring bar, steel, left-hand, Shank Ø / insert size: 16/07 mm**

**Order data**

|              |               |
|--------------|---------------|
| Order number | 260345 16/07  |
| GTIN         | 4045197877987 |
| Item class   | 21T           |

**Description**

Boring bar, steel 16/07 mm Shank Ø  $D_s$ : 16 mm  
 ISO code toolholder: A16Q SDXCR/L07  
 Setting angle  $\kappa$ : 93 degrees  
 suitable indexable insert: DC.. 0702..  
 Minimum pre-drill Ø  $D_{min}$ : 21 mm  
 Centre offset  $L_3$ : 11 mm

**Technical description**

|                               |                |
|-------------------------------|----------------|
| suitable indexable insert     | DC.. 0702..    |
| Centre offset $L_3$           | 11 mm          |
| Pack of insert screws         | 269028 7       |
| ISO code toolholder           | A16Q SDXCR/L07 |
| Head length $L_1$             | 33 mm          |
| Setting angle $\kappa$        | 93 degrees     |
| Insert size                   | 7 mm           |
| Minimum pre-drill Ø $D_{min}$ | 21 mm          |
| Clamping height $L_2$         | 15 mm          |
| Overall length L              | 180 mm         |
| Usable depth T                | 4.3 mm         |
| Shank Ø $D_s$                 | 16 mm          |

|                    |            |
|--------------------|------------|
| Application type   | left-hand  |
| Boring depth up to | 3×D        |
| Standard           | DIN 8024   |
| Through-coolant    | yes        |
| Type of product    | Boring bar |

---

## Accessories

|  |            |
|--|------------|
| Torque screwdriver with scale, to take interchangeable blades maximum torque 500 cNm | 659906 500 |
| PrecisionBit for Torx®, shank E 6.3 Torx® profile TX8                                | 674248 TX8 |
| Set of insert screws 10 pieces   | 269413     |
| Set of insert screws Type 7  | 269028 7   |