

Garant
Boring bar, steel, left-hand, Shank \varnothing / insert size: 20/11 mm

Order data

Order number	260345 20/11
GTIN	4045197877994
Item class	21T

Description

Boring bar, steel 20/11 mm Shank \varnothing D_s : 20 mm
 ISO code toolholder: A20R SDXCR/L11
 Setting angle κ : 93 degrees
 suitable indexable insert: DC.. 11T3..
 Minimum pre-drill \varnothing D_{min} : 25 mm
 Centre offset L_3 : 13 mm

Technical description

Pack of insert screws	269028 21
Centre offset L_3	13 mm
Clamping height L_2	18 mm
suitable indexable insert	DC.. 11T3..
Insert size	11 mm
Head length L_1	40 mm
Setting angle κ	93 degrees
ISO code toolholder	A20R SDXCR/L11
Overall length L	200 mm
Minimum pre-drill \varnothing D_{min}	25 mm
Shank \varnothing D_s	20 mm
Application type	left-hand

Boring depth up to	3xD
Standard	DIN 8024
Through-coolant	yes
Type of product	Boring bar

Accessories

Pack of insert screws 10 pieces	269434
Torque screwdriver with scale, to take interchangeable blades maximum torque 500 cNm	659906 500
PrecisionBit for Torx®, shank E 6.3 Torx® profile TX15	674248 TX15
Set of insert screws Type 21	269028 21