

Garant
Boring bar, steel, left-hand, Shank \varnothing / insert size: 25/11 mm

Order data

Order number	260345 25/11
GTIN	4045197878007
Item class	21T

Description

Boring bar, steel 25/11 mm Shank \varnothing D_s : 25 mm
 ISO code toolholder: A25R SDXCR/L11
 Setting angle κ : 93 degrees
 suitable indexable insert: DC.. 11T3..
 Minimum pre-drill \varnothing D_{min} : 31.5 mm
 Centre offset L_3 : 17 mm

Technical description

Insert size	11 mm
Setting angle κ	93 degrees
Overall length L	200 mm
Centre offset L_3	17 mm
Minimum pre-drill \varnothing D_{min}	31.5 mm
Clamping height L_2	23 mm
Pack of insert screws	269028 21
Head length L_1	50 mm
suitable indexable insert	DC.. 11T3..
ISO code toolholder	A25R SDXCR/L11
Shank \varnothing D_s	25 mm
Application type	left-hand

Boring depth up to	3xD
Standard	DIN 8024
Through-coolant	yes
Type of product	Boring bar

Accessories

Set of insert screws Type 21	269028 21
PrecisionBit for Torx®, shank E 6.3 Torx® profile TX15	674248 TX15
Torque screwdriver with scale, to take interchangeable blades maximum torque 500 cNm	659906 500
Pack of insert screws 10 pieces	269434