



## Boring bar set, steel, with IC, left-hand, Type: SET11



### Order data

Order number	260347 SET11
GTIN	4045197657763
Item class	29W

### Description

#### Supplied with:

Plastic case  
 Through-coolant: yes  
 ISO code toolholder: A16Q SDUCR/L11  
 ISO code toolholder: A20R SDUCR/L11  
 ISO code toolholder: A25R SDUCR/L11  
 suitable indexable insert: DC.. 11T3..  
 Minimum pre-drill  $\varnothing D_{\min}$ : 25 mm  
 Minimum pre-drill  $\varnothing D_{\min}$ : 27 mm

### Technical description

Pack of insert screws	269028 14
ISO code toolholder	A16Q SDUCR/L11
ISO code toolholder	A20R SDUCR/L11
ISO code toolholder	A25R SDUCR/L11
suitable indexable insert	DC.. 11T3..

Clamping height L <sub>2</sub>	15 mm
Clamping height L <sub>2</sub>	18 mm
Clamping height L <sub>2</sub>	23 mm
Minimum pre-drill Ø D <sub>min</sub>	25 mm
Minimum pre-drill Ø D <sub>min</sub>	27 mm
Minimum pre-drill Ø D <sub>min</sub>	32 mm
Centre offset L <sub>3</sub>	13.6 mm
Centre offset L <sub>3</sub>	16 mm
Centre offset L <sub>3</sub>	18.5 mm
Overall length L	180 mm
Overall length L	200 mm
Overall length L	200 mm
Application type	left-hand
Boring depth up to	3×D
Standard	DIN 8024
Through-coolant	yes
Type of product	Boring bar

## Accessories

Torque screwdriver with scale, to take interchangeable blades maximum torque 500 cNm	659906 500
PrecisionBit for Torx®, shank E 6.3 Torx® profile TX15	674248 TX15
Set of insert screws Type 14	269028 14
Set of insert screws 10 pieces	269420
Boring bar steel Shank Ø / insert size 16/07 mm	260343 16/07
Boring bar steel Shank Ø / insert size 16/07 mm	260342 16/07
Boring bar steel Shank Ø / insert size 20/11 mm	260343 20/11
Boring bar steel Shank Ø / insert size 25/11 mm	260343 25/11

Boring bar steel Shank Ø / insert size 20/11 mm

260342 20/11