

Garant
Boring bar, steel, right-hand, Shank \varnothing / insert size: 16/09 mm

Order data

Order number	260724 16/09
GTIN	4045197927781
Item class	21T

Description

Boring bar, steel 16/09 mm Shank $\varnothing D_s$: 16 mm
 ISO code toolholder: A16M SSKCR/L09
 Setting angle κ : 75 degrees
 suitable indexable insert: SC.. 09T3..
 Minimum pre-drill $\varnothing D_{min}$: 20 mm
 Centre offset L_3 : 11 mm

Technical description

Overall length L	150 mm
ISO code toolholder	A16M SSKCR/L09
Pack of insert screws	269028 14
Insert size	9 mm
Setting angle κ	75 degrees
Minimum pre-drill $\varnothing D_{min}$	20 mm
suitable indexable insert	SC.. 09T3..
Clamping height L_2	15.25 mm
Centre offset L_3	11 mm
Shank $\varnothing D_s$	16 mm
Application type	right-hand
Boring depth up to	3xD

Standard	DIN 8024
Through-coolant	yes
Type of product	Boring bar

Accessories

PrecisionBit for Torx®, shank E 6.3 Torx® profile TX15	674248 TX15
Torque screwdriver with scale, to take interchangeable blades maximum torque 500 cNm	659906 500