

**Garant**
**Boring bar, steel, left-hand, Shank  $\varnothing$  / insert size: 16/09 mm**

**Order data**

Order number	260725 16/09
GTIN	4045197927798
Item class	21T

**Description**

Boring bar, steel 16/09 mm Shank  $\varnothing$   $D_s$ : 16 mm  
 ISO code toolholder: A16M SSKCR/L09  
 Setting angle  $\kappa$ : 75 degrees  
 suitable indexable insert: SC.. 09T3..  
 Minimum pre-drill  $\varnothing$   $D_{min}$ : 20 mm  
 Centre offset  $L_3$ : 11 mm

**Technical description**

Centre offset $L_3$	11 mm
Insert size	9 mm
Pack of insert screws	269028 14
Clamping height $L_2$	15.25 mm
Setting angle $\kappa$	75 degrees
Minimum pre-drill $\varnothing$ $D_{min}$	20 mm
suitable indexable insert	SC.. 09T3..
ISO code toolholder	A16M SSKCR/L09
Overall length L	150 mm
Shank $\varnothing$ $D_s$	16 mm
Application type	left-hand
Boring depth up to	3xD

Standard	DIN 8024
Through-coolant	yes
Type of product	Boring bar

---

## Accessories

Torque screwdriver with scale, to take interchangeable blades maximum torque 500 cNm	659906 500
PrecisionBit for Torx®, shank E 6.3 Torx® profile TX15	674248 TX15