

Garant
Boring bar, steel, left-hand, Shank \varnothing / insert size: 20/09 mm

Order data

Order number	260725 20/09
GTIN	4045197945136
Item class	21T

Description

Boring bar, steel 20/09 mm Shank \varnothing D_s: 20 mm
 ISO code toolholder: A20Q SSKCR/L09
 Setting angle κ : 75 degrees
 suitable indexable insert: SC.. 09T3..
 Minimum pre-drill \varnothing D_{min}: 25 mm
 Centre offset L₃: 13 mm

Technical description

Clamping height L ₂	19 mm
Centre offset L ₃	13 mm
Insert size	9 mm
suitable indexable insert	SC.. 09T3..
Setting angle κ	75 degrees
ISO code toolholder	A20Q SSKCR/L09
Overall length L	180 mm
Minimum pre-drill \varnothing D _{min}	25 mm
Pack of insert screws	269028 14
Shank \varnothing D _s	20 mm
Application type	left-hand
Boring depth up to	3×D

Standard	DIN 8024
Through-coolant	yes
Type of product	Boring bar

Accessories

Torque screwdriver with scale, to take interchangeable blades maximum torque 500 cNm	659906 500
PrecisionBit for Torx®, shank E 6.3 Torx® profile TX15	674248 TX15