

**Garant**
**Boring bar carbide, right-hand, Shank  $\varnothing$  / insert size: 10/11 mm**

**Order data**

Order number	260918 10/11
GTIN	4045197653369
Item class	21T

**Description**

Boring bar carbide 10/11 mm Shank  $\varnothing$  D<sub>s</sub>: 10 mm

ISO code toolholder: E10K STFCR/L11

Setting angle  $\kappa$ : 45 degrees

suitable indexable insert: TC.. 1102..

Minimum pre-drill  $\varnothing$  D<sub>min</sub>: 12 mm

Centre offset L<sub>3</sub>: 6 mm

**Technical description**

Minimum pre-drill $\varnothing$ D <sub>min</sub>	12 mm
Pack of insert screws	269028 7
ISO code toolholder	E10K STFCR/L11
suitable indexable insert	TC.. 1102..
Centre offset L <sub>3</sub>	6 mm
Head length L <sub>1</sub>	16 mm
Insert size	11 mm
Overall length L	125 mm
Clamping height L <sub>2</sub>	9.6 mm
Setting angle $\kappa$	45 degrees
Shank $\varnothing$ D <sub>s</sub>	10 mm
Application type	right-hand
Boring depth up to	8×D

Tool material	Carbide
Standard	DIN 8024
Through-coolant	yes
Type of product	Boring bar

---

## Accessories

Set of insert screws 10 pieces	269413
PrecisionBit for Torx®, shank E 6.3 Torx® profile TX8	674248 TX8
Set of insert screws Type 7	269028 7
Torque screwdriver with scale, to take interchangeable blades maximum torque 500 cNm	659906 500