

Garant
Boring bar carbide, right-hand, Shank \varnothing / insert size: 12/11 mm

Order data

Order number	260918 12/11
GTIN	4045197653376
Item class	21T

Description

Boring bar carbide 12/11 mm Shank \varnothing D_s: 12 mm

ISO code toolholder: E12M STFCR/L11

Setting angle κ : 45 degrees

suitable indexable insert: TC.. 1102..

Minimum pre-drill \varnothing D_{min}: 15 mm

Centre offset L₃: 8 mm

Technical description

Minimum pre-drill \varnothing D _{min}	15 mm
ISO code toolholder	E12M STFCR/L11
Centre offset L ₃	8 mm
Head length L ₁	20 mm
Insert size	11 mm
Pack of insert screws	269028 7
suitable indexable insert	TC.. 1102..
Overall length L	150 mm
Clamping height L ₂	11.5 mm
Setting angle κ	45 degrees
Shank \varnothing D _s	12 mm
Application type	right-hand
Boring depth up to	8×D

Tool material	Carbide
Standard	DIN 8024
Through-coolant	yes
Type of product	Boring bar

Accessories

Torque screwdriver with scale, to take interchangeable blades maximum torque 500 cNm	659906 500
Set of insert screws 10 pieces	269413
Set of insert screws Type 7	269028 7
PrecisionBit for Torx®, shank E 6.3 Torx® profile TX8	674248 TX8