

Garant
Boring bar carbide, right-hand, Shank \varnothing / insert size: 16/11 mm

Order data

Order number	260918 16/11
GTIN	4045197653383
Item class	21T

Description

Boring bar carbide 16/11 mm Shank \varnothing D_s: 16 mm

ISO code toolholder: E16R STFCL/L11

Setting angle κ : 45 degrees

suitable indexable insert: TC.. 1102..

Minimum pre-drill \varnothing D_{min}: 19 mm

Centre offset L₃: 10 mm

Technical description

ISO code toolholder	E16R STFCL/L11
Minimum pre-drill \varnothing D _{min}	19 mm
Pack of insert screws	269028 7
suitable indexable insert	TC.. 1102..
Insert size	11 mm
Head length L ₁	25 mm
Centre offset L ₃	10 mm
Overall length L	200 mm
Clamping height L ₂	15.4 mm
Setting angle κ	45 degrees
Shank \varnothing D _s	16 mm
Application type	right-hand
Boring depth up to	8×D

Tool material	Carbide
Standard	DIN 8024
Through-coolant	yes
Type of product	Boring bar

Accessories

Set of insert screws Type 7	269028 7
Set of insert screws 10 pieces	269413
Torque screwdriver with scale, to take interchangeable blades maximum torque 500 cNm	659906 500
PrecisionBit for Torx®, shank E 6.3 Torx® profile TX8	674248 TX8