

Garant
Boring bar carbide, left-hand, Shank \varnothing / insert size: 10/11 mm

Order data

Order number	260919 10/11
GTIN	4045197653390
Item class	21T

Description

Boring bar carbide 10/11 mm Shank $\varnothing D_s$: 10 mm
 ISO code toolholder: E10K STFRCR/L11
 Setting angle κ : 45 degrees
 suitable indexable insert: TC.. 1102..
 Minimum pre-drill $\varnothing D_{\min}$: 12 mm
 Centre offset L_3 : 6 mm

Technical description

Pack of insert screws	269028 7
ISO code toolholder	E10K STFRCR/L11
suitable indexable insert	TC.. 1102..
Head length L_1	16 mm
Centre offset L_3	6 mm
Minimum pre-drill $\varnothing D_{\min}$	12 mm
Insert size	11 mm
Overall length L	125 mm
Clamping height L_2	9.6 mm
Setting angle κ	45 degrees
Shank $\varnothing D_s$	10 mm
Application type	left-hand
Boring depth up to	8xD

Tool material	Carbide
Standard	DIN 8024
Through-coolant	yes
Type of product	Boring bar

Accessories

Torque screwdriver with scale, to take interchangeable blades maximum torque 500 cNm	659906 500
Set of insert screws 10 pieces	269413
Set of insert screws Type 7	269028 7
PrecisionBit for Torx®, shank E 6.3 Torx® profile TX8	674248 TX8