

Garant
Boring bar carbide, left-hand, Shank \varnothing / insert size: 16/11 mm

Order data

Order number	260919 16/11
GTIN	4045197653413
Item class	21T

Description

Boring bar carbide 16/11 mm Shank $\varnothing D_s$: 16 mm

ISO code toolholder: E16R STFCR/L11

Setting angle κ : 45 degrees

suitable indexable insert: TC.. 1102..

Minimum pre-drill $\varnothing D_{min}$: 19 mm

Centre offset L_3 : 10 mm

Technical description

Insert size	11 mm
ISO code toolholder	E16R STFCR/L11
Minimum pre-drill $\varnothing D_{min}$	19 mm
Pack of insert screws	269028 7
Head length L_1	25 mm
suitable indexable insert	TC.. 1102..
Centre offset L_3	10 mm
Overall length L	200 mm
Clamping height L_2	15.4 mm
Setting angle κ	45 degrees
Shank $\varnothing D_s$	16 mm
Application type	left-hand
Boring depth up to	8xD

Tool material	Carbide
Standard	DIN 8024
Through-coolant	yes
Type of product	Boring bar

Accessories

Torque screwdriver with scale, to take interchangeable blades maximum torque 500 cNm	659906 500
Set of insert screws 10 pieces	269413
Set of insert screws Type 7	269028 7
PrecisionBit for Torx®, shank E 6.3 Torx® profile TX8	674248 TX8