

Garant
Boring bar HSS, right-hand, Shank \varnothing / insert size: 20/11 mm

Order data

Order number	260922 20/11
GTIN	4045197653451
Item class	21T

Description

Boring bar HSS 20/11 mm Shank $\varnothing D_s$: 20 mm
 ISO code toolholder: AH20R STF/CR/L11
 Setting angle κ : 45 degrees
 suitable indexable insert: TC.. 1102..
 Minimum pre-drill $\varnothing D_{min}$: 23 mm
 Centre offset L_3 : 13 mm

Technical description

Centre offset L_3	13 mm
Pack of insert screws	269028 7
Minimum pre-drill $\varnothing D_{min}$	23 mm
Head length L_1	32 mm
ISO code toolholder	AH20R STF/CR/L11
suitable indexable insert	TC.. 1102..
Insert size	11 mm
Overall length L	200 mm
Clamping height L_2	18 mm
Setting angle κ	45 degrees
Shank $\varnothing D_s$	20 mm
Application type	right-hand
Boring depth up to	5×D

Tool material	HSS
Standard	DIN 8024
Through-coolant	yes
Type of product	Boring bar

Accessories

Torque screwdriver with scale, to take interchangeable blades maximum torque 500 cNm	659906 500
PrecisionBit for Torx®, shank E 6.3 Torx® profile TX8	674248 TX8
Set of insert screws 10 pieces	269413
Set of insert screws Type 7	269028 7