

**Garant**
**Boring bar HSS, left-hand, Shank  $\varnothing$  / insert size: 10/11 mm**

**Order data**

Order number	260923 10/11
GTIN	4045197653475
Item class	21T

**Description**

Boring bar HSS 10/11 mm Shank  $\varnothing D_s$ : 10 mm

ISO code toolholder: AH10K STFCR/L11

Setting angle  $\kappa$ : 45 degrees

suitable indexable insert: TC.. 1102..

Minimum pre-drill  $\varnothing D_{\min}$ : 12 mm

Centre offset  $L_3$ : 7 mm

**Technical description**

Insert size	11 mm
Centre offset $L_3$	7 mm
Minimum pre-drill $\varnothing D_{\min}$	12 mm
Head length $L_1$	16 mm
suitable indexable insert	TC.. 1102..
ISO code toolholder	AH10K STFCR/L11
Pack of insert screws	269028 7
Overall length L	125 mm
Clamping height $L_2$	9 mm
Setting angle $\kappa$	45 degrees
Shank $\varnothing D_s$	10 mm
Application type	left-hand
Boring depth up to	5xD

Tool material	HSS
Standard	DIN 8024
Through-coolant	yes
Type of product	Boring bar

---

## Accessories

Torque screwdriver with scale, to take interchangeable blades maximum torque 500 cNm	659906 500
PrecisionBit for Torx®, shank E 6.3 Torx® profile TX8	674248 TX8
Set of insert screws Type 7	269028 7
Set of insert screws 10 pieces	269413