

Garant
Boring bar HSS, left-hand, Shank \varnothing / insert size: 12/11 mm

Order data

Order number	260923 12/11
GTIN	4045197653482
Item class	21T

Description

Boring bar HSS 12/11 mm Shank $\varnothing D_s$: 12 mm

ISO code toolholder: AH12M STFCL/L11

Setting angle κ : 45 degrees

suitable indexable insert: TC.. 1102..

Minimum pre-drill $\varnothing D_{\min}$: 14 mm

Centre offset L_3 : 9 mm

Technical description

Centre offset L_3	9 mm
Head length L_1	20 mm
Pack of insert screws	269028 7
ISO code toolholder	AH12M STFCL/L11
suitable indexable insert	TC.. 1102..
Minimum pre-drill $\varnothing D_{\min}$	14 mm
Insert size	11 mm
Overall length L	150 mm
Clamping height L_2	11 mm
Setting angle κ	45 degrees
Shank $\varnothing D_s$	12 mm
Application type	left-hand
Boring depth up to	5xD

Tool material	HSS
Standard	DIN 8024
Through-coolant	yes
Type of product	Boring bar

Accessories

Set of insert screws 10 pieces	269413
Set of insert screws Type 7	269028 7
Torque screwdriver with scale, to take interchangeable blades maximum torque 500 cNm	659906 500
PrecisionBit for Torx®, shank E 6.3 Torx® profile TX8	674248 TX8