



Boring bar steel, right-hand, Shank Ø / insert size: 12/11 mm



Order data

Order number	260930 12/11
GTIN	4960664541799
Item class	25U

Description

Version:

Streamlined flutes for improved chip evacuation, reduced tendency to vibrate, stable machining conditions.

Through-coolant: yes

Shank Ø D_s : 12 mm

ISO code toolholder: A12M STLCR/L11

Setting angle κ : 95 degrees

suitable indexable insert: TC.. 1102..

Minimum pre-drill Ø D_{min} : 14 mm

Centre offset L_3 : 7.2 mm

Technical description

Minimum pre-drill Ø D_{min}	14 mm
Centre offset L_3	7.2 mm
ISO code toolholder	A12M STLCR/L11
Insert screw	269022 4
suitable indexable insert	TC.. 1102..
Insert size	11 mm
Overall length L	150 mm
Clamping height L_2	11 mm
Setting angle κ	95 degrees
Shank Ø D_s	12 mm

Application type	right-hand
Boring depth up to	5×D
Standard	DIN 8024
Through-coolant	yes
Type of product	Boring bar

Accessories

Clamping screw Type 4	269022 4
Clamping screw	269407
Torque screwdriver with scale, to take interchangeable blades maximum torque 500 cNm	659906 500
PrecisionBit for Torx®, shank E 6.3 Torx® profile TX8	674248 TX8