



Boring bar steel, right-hand, Shank \varnothing / insert size: 20/11 mm



Order data

Order number	260930 20/11
GTIN	4960664541836
Item class	25U

Description

Version:

Streamlined flutes for improved chip evacuation, reduced tendency to vibrate, stable machining conditions.

Through-coolant: yes

Shank $\varnothing D_s$: 20 mm

ISO code toolholder: A20R STLCR/L11

Setting angle κ : 95 degrees

suitable indexable insert: TC.. 1102..

Minimum pre-drill $\varnothing D_{min}$: 22 mm

Centre offset L_3 : 11.2 mm

Technical description

ISO code toolholder	A20R STLCR/L11
Minimum pre-drill $\varnothing D_{min}$	22 mm
Insert screw	269022 4
Insert size	11 mm
suitable indexable insert	TC.. 1102..
Centre offset L_3	11.2 mm
Overall length L	200 mm
Clamping height L_2	19 mm
Setting angle κ	95 degrees
Shank $\varnothing D_s$	20 mm

Application type	right-hand
Boring depth up to	5×D
Standard	DIN 8024
Through-coolant	yes
Type of product	Boring bar

Accessories

Torque screwdriver with scale, to take interchangeable blades maximum torque 500 cNm	659906 500
PrecisionBit for Torx®, shank E 6.3 Torx® profile TX8	674248 TX8
Clamping screw	269407
Clamping screw Type 4	269022 4