



Boring bar steel, left-hand, Shank Ø / insert size: 16/11 mm



Order data

Order number	260931 16/11
GTIN	4960664541829
Item class	25U

Description

Version:

Streamlined flutes for improved chip evacuation, reduced tendency to vibrate, stable machining conditions.

Through-coolant: yes

Shank Ø D_s: 16 mm

ISO code toolholder: A16Q STLCR/L11

Setting angle κ: 95 degrees

suitable indexable insert: TC.. 1102..

Minimum pre-drill Ø D_{min}: 18 mm

Centre offset L₃: 9.2 mm

Technical description

Centre offset L ₃	9.2 mm
ISO code toolholder	A16Q STLCR/L11
Insert screw	269022 4
Minimum pre-drill Ø D _{min}	18 mm
Insert size	11 mm
suitable indexable insert	TC.. 1102..
Overall length L	180 mm
Clamping height L ₂	15 mm
Setting angle κ	95 degrees
Shank Ø D _s	16 mm

Application type	left-hand
Boring depth up to	5×D
Standard	DIN 8024
Through-coolant	yes
Type of product	Boring bar

Accessories

Clamping screw	269407
PrecisionBit for Torx®, shank E 6.3 Torx® profile TX8	674248 TX8
Torque screwdriver with scale, to take interchangeable blades maximum torque 500 cNm	659906 500
Clamping screw Type 4	269022 4