

Garant
Boring bar steel, right-hand, Shank \varnothing / insert size: 10/11 mm

Order data

Order number	260934 10/11
GTIN	4045197653529
Item class	21T

Description

Boring bar steel 10/11 mm Shank $\varnothing D_s$: 10 mm
 ISO code toolholder: A10K STFCR/L11
 Setting angle κ : 45 degrees
 suitable indexable insert: TC.. 1102..
 Minimum pre-drill $\varnothing D_{min}$: 13 mm
 Centre offset L_3 : 7 mm

Technical description

Centre offset L_3	7 mm
Pack of insert screws	269028 7
Minimum pre-drill $\varnothing D_{min}$	13 mm
suitable indexable insert	TC.. 1102..
Head length L_1	22.8 mm
ISO code toolholder	A10K STFCR/L11
Insert size	11 mm
Overall length L	125 mm
Clamping height L_2	9 mm
Setting angle κ	45 degrees
Shank $\varnothing D_s$	10 mm
Application type	right-hand

Boring depth up to	3xD
Standard	DIN 8024
Through-coolant	yes
Type of product	Boring bar

Accessories

Set of insert screws Type 7	269028 7
PrecisionBit for Torx®, shank E 6.3 Torx® profile TX8	674248 TX8
Set of insert screws 10 pieces	269413
Torque screwdriver with scale, to take interchangeable blades maximum torque 500 cNm	659906 500