

Garant
Boring bar steel, right-hand, Shank \varnothing / insert size: 16/11 mm

Order data

| | |
|--------------|---------------|
| Order number | 260934 16/11 |
| GTIN | 4045197653543 |
| Item class | 21T |

Description

Boring bar steel 16/11 mm Shank $\varnothing D_s$: 16 mm
 ISO code toolholder: A16Q STF CR/L11
 Setting angle κ : 45 degrees
 suitable indexable insert: TC.. 1102..
 Minimum pre-drill $\varnothing D_{min}$: 20 mm
 Centre offset L_3 : 11 mm

Technical description

| | |
|---|-----------------|
| Centre offset L_3 | 11 mm |
| Pack of insert screws | 269028 7 |
| Minimum pre-drill $\varnothing D_{min}$ | 20 mm |
| suitable indexable insert | TC.. 1102.. |
| Head length L_1 | 26.7 mm |
| Insert size | 11 mm |
| ISO code toolholder | A16Q STF CR/L11 |
| Overall length L | 180 mm |
| Clamping height L_2 | 15 mm |
| Setting angle κ | 45 degrees |
| Shank $\varnothing D_s$ | 16 mm |
| Application type | right-hand |

| | |
|--------------------|------------|
| Boring depth up to | 3xD |
| Standard | DIN 8024 |
| Through-coolant | yes |
| Type of product | Boring bar |

Accessories

| | |
|--|------------|
| PrecisionBit for Torx®, shank E 6.3 Torx® profile TX8 | 674248 TX8 |
| Set of insert screws 10 pieces | 269413 |
| Set of insert screws Type 7 | 269028 7 |
| Torque screwdriver with scale, to take interchangeable blades maximum torque 500 cNm | 659906 500 |