

Garant
Boring bar steel, right-hand, Shank \varnothing / insert size: 20/16 mm

Order data

Order number	260934 20/16
GTIN	4045197653550
Item class	21T

Description

Boring bar steel 20/16 mm Shank $\varnothing D_s$: 20 mm
 ISO code toolholder: A20R STFCL/L16
 Setting angle κ : 45 degrees
 suitable indexable insert: TC.. 16T3..
 Minimum pre-drill $\varnothing D_{min}$: 25 mm
 Centre offset L_3 : 13 mm

Technical description

Minimum pre-drill $\varnothing D_{min}$	25 mm
Centre offset L_3	13 mm
Pack of insert screws	269028 8
Head length L_1	36.6 mm
ISO code toolholder	A20R STFCL/L16
Insert size	16 mm
suitable indexable insert	TC.. 16T3..
Overall length L	200 mm
Clamping height L_2	18 mm
Setting angle κ	45 degrees
Shank $\varnothing D_s$	20 mm
Application type	right-hand

Boring depth up to	3xD
Standard	DIN 8024
Through-coolant	yes
Type of product	Boring bar

Accessories

Set of insert screws Type 8	269028 8
PrecisionBit for Torx®, shank E 6.3 Torx® profile TX15	674248 TX15
Set of insert screws 10 pieces	269414
Torque screwdriver with scale, to take interchangeable blades maximum torque 500 cNm	659906 500