

Garant

Boring bar steel, right-hand, Shank \varnothing / insert size: 40/16 mm



Order data

Order number	260934 40/16
GTIN	4045197656063
Item class	21T

Description

Boring bar steel 40/16 mm Shank $\varnothing D_s$: 40 mm

ISO code toolholder: A40T STF/CR/L16

Setting angle κ : 45 degrees

suitable indexable insert: TC.. 16T3..

Minimum pre-drill $\varnothing D_{min}$: 49 mm

Centre offset L_3 : 27 mm

Technical description

ISO code toolholder	A40T STF/CR/L16
Insert size	16 mm
suitable indexable insert	TC.. 16T3..
Shim	269005 7
Shim screw	269013 2
Pack of insert screws	269028 24
Centre offset L_3	27 mm
Minimum pre-drill $\varnothing D_{min}$	49 mm
Head length L_1	37.5 mm
Overall length L	300 mm
Clamping height L_2	39 mm
Setting angle κ	45 degrees

Shank Ø D _s	40 mm
Application type	right-hand
Boring depth up to	3×D
Standard	DIN 8024
Through-coolant	yes
Type of product	Boring bar

Accessories

Set of insert screws Type 8	269028 8
Set of insert screws Type 24	269028 24
PrecisionBit for Torx®, shank E 6.3 Torx® profile TX15	674248 TX15
Torque screwdriver with scale, to take interchangeable blades maximum torque 500 cNm	659906 500
Set of insert screws 10 pieces	269414
Shim screw Type 2	269013 2
Shim screw	269200
Shim	269040
Shim Type 7	269005 7
Set of insert screws 10 pieces	269468