

**Garant**
**Boring bar steel, left-hand, Shank  $\varnothing$  / insert size: 10/11 mm**

**Order data**

Order number	260935 10/11
GTIN	4045197653581
Item class	21T

**Description**

Boring bar steel 10/11 mm Shank  $\varnothing D_s$ : 10 mm  
 ISO code toolholder: A10K STFCL/L11  
 Setting angle  $\kappa$ : 45 degrees  
 suitable indexable insert: TC.. 1102..  
 Minimum pre-drill  $\varnothing D_{min}$ : 13 mm  
 Centre offset  $L_3$ : 7 mm

**Technical description**

Insert size	11 mm
Pack of insert screws	269028 7
ISO code toolholder	A10K STFCL/L11
Centre offset $L_3$	7 mm
suitable indexable insert	TC.. 1102..
Minimum pre-drill $\varnothing D_{min}$	13 mm
Head length $L_1$	22.8 mm
Overall length L	125 mm
Clamping height $L_2$	9 mm
Setting angle $\kappa$	45 degrees
Shank $\varnothing D_s$	10 mm
Application type	left-hand

Boring depth up to	3xD
Standard	DIN 8024
Through-coolant	yes
Type of product	Boring bar

---

## Accessories

Torque screwdriver with scale, to take interchangeable blades maximum torque 500 cNm	659906 500
Set of insert screws Type 7	269028 7
Set of insert screws 10 pieces	269413
PrecisionBit for Torx®, shank E 6.3 Torx® profile TX8	674248 TX8