

Garant
Boring bar steel, left-hand, Shank \varnothing / insert size: 16/11 mm

Order data

Order number	260935 16/11
GTIN	4045197653604
Item class	21T

Description

Boring bar steel 16/11 mm Shank $\varnothing D_s$: 16 mm
 ISO code toolholder: A16Q STFCR/L11
 Setting angle κ : 45 degrees
 suitable indexable insert: TC.. 1102..
 Minimum pre-drill $\varnothing D_{min}$: 20 mm
 Centre offset L_3 : 11 mm

Technical description

Centre offset L_3	11 mm
Minimum pre-drill $\varnothing D_{min}$	20 mm
Head length L_1	26.7 mm
ISO code toolholder	A16Q STFCR/L11
Pack of insert screws	269028 7
suitable indexable insert	TC.. 1102..
Insert size	11 mm
Overall length L	180 mm
Clamping height L_2	15 mm
Setting angle κ	45 degrees
Shank $\varnothing D_s$	16 mm
Application type	left-hand

Boring depth up to	3xD
Standard	DIN 8024
Through-coolant	yes
Type of product	Boring bar

Accessories

Set of insert screws 10 pieces	269413
Set of insert screws Type 7	269028 7
PrecisionBit for Torx®, shank E 6.3 Torx® profile TX8	674248 TX8
Torque screwdriver with scale, to take interchangeable blades maximum torque 500 cNm	659906 500