

Garant
Boring bar steel, left-hand, Shank \varnothing / insert size: 20/16 mm

Order data

Order number	260935 20/16
GTIN	4045197653611
Item class	21T

Description

Boring bar steel 20/16 mm Shank \varnothing D_s : 20 mm
 ISO code toolholder: A20R STFCL/L16
 Setting angle κ : 45 degrees
 suitable indexable insert: TC.. 16T3..
 Minimum pre-drill \varnothing D_{min} : 25 mm
 Centre offset L_3 : 13 mm

Technical description

Minimum pre-drill \varnothing D_{min}	25 mm
suitable indexable insert	TC.. 16T3..
Centre offset L_3	13 mm
Head length L_1	36.6 mm
ISO code toolholder	A20R STFCL/L16
Pack of insert screws	269028 8
Insert size	16 mm
Overall length L	200 mm
Clamping height L_2	18 mm
Setting angle κ	45 degrees
Shank \varnothing D_s	20 mm
Application type	left-hand

Boring depth up to	3xD
Standard	DIN 8024
Through-coolant	yes
Type of product	Boring bar

Accessories

Set of insert screws Type 8	269028 8
PrecisionBit for Torx®, shank E 6.3 Torx® profile TX15	674248 TX15
Torque screwdriver with scale, to take interchangeable blades maximum torque 500 cNm	659906 500
Set of insert screws 10 pieces	269414