

Garant
Boring bar steel, left-hand, Shank \varnothing / insert size: 25/16 mm

Order data

Order number	260935 25/16
GTIN	4045197653628
Item class	21T

Description

Boring bar steel 25/16 mm Shank $\varnothing D_s$: 25 mm
 ISO code toolholder: A25R STF CR/L16
 Setting angle κ : 45 degrees
 suitable indexable insert: TC.. 16T3..
 Minimum pre-drill $\varnothing D_{min}$: 32 mm
 Centre offset L_3 : 17 mm

Technical description

suitable indexable insert	TC.. 16T3..
Head length L_1	41 mm
ISO code toolholder	A25R STF CR/L16
Minimum pre-drill $\varnothing D_{min}$	32 mm
Pack of insert screws	269028 8
Insert size	16 mm
Centre offset L_3	17 mm
Overall length L	200 mm
Clamping height L_2	23 mm
Setting angle κ	45 degrees
Shank $\varnothing D_s$	25 mm
Application type	left-hand

Boring depth up to	3xD
Standard	DIN 8024
Through-coolant	yes
Type of product	Boring bar

Accessories

Set of insert screws 10 pieces	269414
Set of insert screws Type 8	269028 8
Torque screwdriver with scale, to take interchangeable blades maximum torque 500 cNm	659906 500
PrecisionBit for Torx®, shank E 6.3 Torx® profile TX15	674248 TX15