

### eco screw-on toolholder, left-hand, Shank size / insert size: 20/16 mm



### **Order data**

Order number	261103 20/16
GTIN	4045197945297
Item class	21U

## **Description**

#### **Version:**

With internal coolant feed right to the cutting edge. Cooling by means of precision nozzles effectively and efficiently reduces the thermal loading, since the coolant stream is optimally directed between the chip and cutting edge. This results in higher productivity, longer tool life and increased process reliability.

With flank face cooling.

#### Note:

Coolant transfer only in conjunction with GARANT eco-system toolholders No. 317900 – 319886.

Through-coolant: yes

ISO code toolholder: SVJBR/L 2020X16 suitable indexable insert: VB.. 1604..

Head length L<sub>1</sub>: 40 mm Overall length L: 99 mm

Pack of insert screws: 269028 28

Shim: 259033 5

### **Technical description**

ISO code toolholder	SVJBR/L 2020X16
Shim screw	269013 1
Head length L <sub>1</sub>	40 mm
Shank size	20 mm
Pack of insert screws	269028 28

suitable indexable insert	VB 1604
Overall length L	99 mm
Insert size	16 mm
Shim	259033 5
Application type	left-hand
Standard	DIN ISO 5610
Through-coolant	yes
Setting angle κ	93 degrees
Type of product	Boring bar

# Accessories

PrecisionBit for Torx®, shank E 6.3 Torx® profile TX15	674248 TX15
Torque screwdriver with scale, to take interchangeable blades maximum torque 500 cNm	659906 500