

Garant
Boring bar steel, right-hand, Shank Ø / insert size: 16/11 mm

Order data

Order number	261124 16/11
GTIN	4045197778369
Item class	21T

Description

Boring bar steel 16/11 mm Shank Ø D_s : 16 mm
 ISO code toolholder: A16M SVJBR/L11
 Setting angle κ : 142 degrees
 suitable indexable insert: VB.. 1103..
 Minimum pre-drill Ø D_{min} : 22 mm
 Centre offset L_3 : 2 mm

Technical description

Pack of insert screws	269028 7
Clamping height L_2	15 mm
ISO code toolholder	A16M SVJBR/L11
Overhang L_1 recessed holders	31.4 mm
Overall length L	150 mm
suitable indexable insert	VB.. 1103..
Insert size	11 mm
Minimum pre-drill Ø D_{min}	22 mm
Neck width	9.5 mm
Setting angle κ	142 degrees
Centre offset L_3	2 mm
Shank Ø D_s	16 mm

Application type	right-hand
Boring depth up to	3×D
Standard	DIN 8024
Through-coolant	yes
Type of product	Boring bar

Accessories

Set of insert screws 10 pieces	269413
PrecisionBit for Torx®, shank E 6.3 Torx® profile TX8	674248 TX8
Torque screwdriver with scale, to take interchangeable blades maximum torque 500 cNm	659906 500
Set of insert screws Type 7	269028 7