

Garant
Boring bar steel, right-hand, Shank \varnothing / insert size: 20/11 mm

Order data

Order number	261124 20/11
GTIN	4045197778376
Item class	21T

Description

Boring bar steel 20/11 mm Shank $\varnothing D_s$: 20 mm
 ISO code toolholder: A20Q SVJBR/L11
 Setting angle κ : 142 degrees
 suitable indexable insert: VB.. 1103..
 Minimum pre-drill $\varnothing D_{min}$: 25 mm
 Centre offset L_3 : 2 mm

Technical description

Overall length L	180 mm
Pack of insert screws	269028 7
Neck width	11 mm
ISO code toolholder	A20Q SVJBR/L11
Centre offset L_3	2 mm
Minimum pre-drill $\varnothing D_{min}$	25 mm
Overhang L_1 recessed holders	38 mm
Setting angle κ	142 degrees
Clamping height L_2	19 mm
suitable indexable insert	VB.. 1103..
Insert size	11 mm
Shank $\varnothing D_s$	20 mm

Application type	right-hand
Boring depth up to	3×D
Standard	DIN 8024
Through-coolant	yes
Type of product	Boring bar

Accessories

Set of insert screws 10 pieces	269413
Torque screwdriver with scale, to take interchangeable blades maximum torque 500 cNm	659906 500
PrecisionBit for Torx®, shank E 6.3 Torx® profile TX8	674248 TX8
Set of insert screws Type 7	269028 7