

**Garant**
**Boring bar steel, right-hand, Shank  $\varnothing$  / insert size: 16/11 mm**

**Order data**

Order number	261130 16/11
GTIN	4045197656094
Item class	21T

**Description**

Boring bar steel 16/11 mm Shank  $\varnothing D_s$ : 16 mm  
 ISO code toolholder: A16Q SVQBR/L11  
 Setting angle  $\kappa$ : 107.5 degrees  
 suitable indexable insert: VB.. 1103..  
 Minimum pre-drill  $\varnothing D_{min}$ : 21 mm  
 Centre offset  $L_3$ : 11 mm

**Technical description**

ISO code toolholder	A16Q SVQBR/L11
Insert size	11 mm
Minimum pre-drill $\varnothing D_{min}$	21 mm
Pack of insert screws	269028 22
Head length $L_1$	16.5 mm
suitable indexable insert	VB.. 1103..
Centre offset $L_3$	11 mm
Overall length $L$	180 mm
Clamping height $L_2$	15.5 mm
Setting angle $\kappa$	107.5 degrees
Shank $\varnothing D_s$	16 mm
Application type	right-hand

Boring depth up to	3xD
Standard	DIN 8024
Through-coolant	yes
Type of product	Boring bar

---

## Accessories

Set of insert screws Type 22	269028 22
Torque screwdriver with scale, to take interchangeable blades maximum torque 500 cNm	659906 500
Set of insert screws 10 pieces	269440
PrecisionBit for Torx®, shank E 6.3 Torx® profile TX8	674248 TX8