

## Garant

### Boring bar steel, right-hand, Shank $\varnothing$ / insert size: 25/16 mm



#### Order data

Order number	261130 25/16
GTIN	4045197653659
Item class	21T

#### Description

Boring bar steel 25/16 mm Shank  $\varnothing D_s$ : 25 mm  
 ISO code toolholder: A25R SVQBR/L16  
 Setting angle  $\kappa$ : 107.5 degrees  
 suitable indexable insert: VB.. 1604..  
 Minimum pre-drill  $\varnothing D_{min}$ : 32 mm  
 Centre offset  $L_3$ : 17 mm

#### Technical description

Pack of insert screws	269028 8
Insert size	16 mm
Centre offset $L_3$	17 mm
ISO code toolholder	A25R SVQBR/L16
Head length $L_1$	40 mm
Minimum pre-drill $\varnothing D_{min}$	32 mm
suitable indexable insert	VB.. 1604..
Overall length L	200 mm
Clamping height $L_2$	23 mm
Setting angle $\kappa$	107.5 degrees
Shank $\varnothing D_s$	25 mm
Application type	right-hand

Boring depth up to	3xD
Standard	DIN 8024
Through-coolant	yes
Type of product	Boring bar

---

## Accessories

Torque screwdriver with scale, to take interchangeable blades maximum torque 500 cNm	659906 500
Set of insert screws Type 8	269028 8
Set of insert screws 10 pieces	269414
PrecisionBit for Torx®, shank E 6.3 Torx® profile TX15	674248 TX15