

Garant
Boring bar, steel, right-hand, Shank \varnothing / insert size: 40/16 mm

Order data

Order number	261132 40/16
GTIN	4045197878052
Item class	21T

Description

Boring bar, steel 40/16 mm Shank \varnothing D₅: 40 mm
 ISO code toolholder: A40T SVUBR/L16
 Setting angle κ : 93 degrees
 suitable indexable insert: VB.. 1604..
 Minimum pre-drill \varnothing D_{min}: 49 mm
 Centre offset L₃: 27 mm

Technical description

Minimum pre-drill \varnothing D _{min}	49 mm
Clamping height L ₂	39 mm
Pack of insert screws	269028 2
Head length L ₁	40 mm
Shim screw	269013 2
Insert size	16 mm
suitable indexable insert	VB.. 1604..
ISO code toolholder	A40T SVUBR/L16
Centre offset L ₃	27 mm
Shim	269005 8
Overall length L	300 mm
Setting angle κ	93 degrees

Shank $\varnothing D_s$	40 mm
Application type	right-hand
Boring depth up to	3xD
Standard	DIN 8024
Through-coolant	yes
Type of product	Boring bar

Accessories

Set of insert screws Type 22	269028 22
Shim screw	269200
Shim Type 8	269005 8
PrecisionBit for Torx®, shank E 6.3 Torx® profile TX15	674248 TX15
Torque screwdriver with scale, to take interchangeable blades maximum torque 500 cNm	659906 500
Shim	269050
Shim screw Type 2	269013 2
Set of insert screws 10 pieces	269440