

Garant
Boring bar, steel, left-hand, Shank \varnothing / insert size: 32/16 mm

Order data

Order number	261133 32/16
GTIN	4045197878090
Item class	21T

Description

Boring bar, steel 32/16 mm Shank \varnothing D_s : 32 mm
 ISO code toolholder: A32S SVUBR/L16
 Setting angle κ : 93 degrees
 suitable indexable insert: VB.. 1604..
 Minimum pre-drill \varnothing D_{min} : 40 mm
 Centre offset L_3 : 22 mm

Technical description

Pack of insert screws	269028 2
Minimum pre-drill \varnothing D_{min}	40 mm
Centre offset L_3	22 mm
Shim	269005 8
ISO code toolholder	A32S SVUBR/L16
Setting angle κ	93 degrees
Clamping height L_2	31 mm
Insert size	16 mm
Shim screw	269013 2
Overall length L	250 mm
suitable indexable insert	VB.. 1604..
Head length L_1	33.5 mm

Shank $\varnothing D_s$	32 mm
Application type	left-hand
Boring depth up to	3xD
Standard	DIN 8024
Through-coolant	yes
Type of product	Boring bar

Accessories

Set of insert screws 10 pieces	269440
Torque screwdriver with scale, to take interchangeable blades maximum torque 500 cNm	659906 500
Shim Type 8	269005 8
Set of insert screws Type 22	269028 22
PrecisionBit for Torx®, shank E 6.3 Torx® profile TX15	674248 TX15
Shim screw	269200
Shim	269050
Shim screw Type 2	269013 2