

**Garant**
**Boring bar, steel, left-hand, Shank  $\varnothing$  / insert size: 40/16 mm**

**Order data**

Order number	261133 40/16
GTIN	4045197878106
Item class	21T

**Description**

Boring bar, steel 40/16 mm Shank  $\varnothing$   $D_3$ : 40 mm  
 ISO code toolholder: A40T SVUBR/L16  
 Setting angle  $\kappa$ : 93 degrees  
 suitable indexable insert: VB.. 1604..  
 Minimum pre-drill  $\varnothing$   $D_{\min}$ : 49 mm  
 Centre offset  $L_3$ : 27 mm

**Technical description**

suitable indexable insert	VB.. 1604..
Head length $L_1$	40 mm
Centre offset $L_3$	27 mm
Shim screw	269013 2
Setting angle $\kappa$	93 degrees
Shim	269005 8
Pack of insert screws	269028 2
Insert size	16 mm
Minimum pre-drill $\varnothing$ $D_{\min}$	49 mm
Clamping height $L_2$	39 mm
Overall length $L$	300 mm
ISO code toolholder	A40T SVUBR/L16

Shank $\varnothing D_s$	40 mm
Application type	left-hand
Boring depth up to	3xD
Standard	DIN 8024
Through-coolant	yes
Type of product	Boring bar

---

## Accessories

Set of insert screws Type 22	269028 22
Shim	269050
Shim screw	269200
Torque screwdriver with scale, to take interchangeable blades maximum torque 500 cNm	659906 500
Shim screw Type 2	269013 2
Shim Type 8	269005 8
PrecisionBit for Torx®, shank E 6.3 Torx® profile TX15	674248 TX15
Set of insert screws 10 pieces	269440