

### Cutting head, left-hand, Shank size / insert size: 20/11 mm



#### **Order data**

| Order number | 261305 20/11  |
|--------------|---------------|
| GTIN         | 4045197945242 |
| Item class   | 21U           |

### **Description**

#### **Version:**

GARANT eco system screw-on toolholder with internal coolant feed to the cutting edge. Cooling by means of precision nozzles effectively and efficiently reduces the thermal loading, since the coolant stream is optimally directed between the chip and cutting edge. This results in higher productivity, longer tool life and greater process reliability. With flank face cooling.

#### Note:

Coolant transfer only in conjunction with GARANT eco-system toolholders No.317900 – 319886.

Through-coolant: yes

ISO code toolholder: SVJCR/L 2020X11 suitable indexable insert: VC.. 1103..

Functional width L₄: 25 mm Head length L₁: 40 mm Overall length L: 99 mm

Pack of insert screws: 269023 1

## **Technical description**

| Head length L <sub>1</sub>      | 40 mm    |
|---------------------------------|----------|
| Insert size                     | 11 mm    |
| Pack of insert screws           | 269023 1 |
| Shank size                      | 20 mm    |
| Overall length L                | 99 mm    |
| Functional width L <sub>4</sub> | 25 mm    |



| ISO code toolholder       | SVJCR/L 2020X11 |
|---------------------------|-----------------|
| suitable indexable insert | VC 1103         |
| Application type          | left-hand       |
| Standard                  | DIN ISO 5610    |
| Through-coolant           | yes             |
| Setting angle κ           | 93 degrees      |
| Type of product           | Boring bar      |

# **Accessories**

| PrecisionBit for Torx®, shank E 6.3 Torx® profile TX8                                | 674248 TX8 |
|--|------------|
| Torque screwdriver with scale, to take interchangeable blades maximum torque 500 cNm | 659906 500 |