

Garant
Boring bar HSS, right-hand, Shank \varnothing / insert size: 16/11 mm

Order data

Order number	261330 16/11
GTIN	4045197653956
Item class	21T

Description

Boring bar HSS 16/11 mm Shank \varnothing D_s: 16 mm
 ISO code toolholder: AH16M SVJCR/L11
 Cutting point / joint: 16 mm
 Setting angle κ : 142 degrees
 suitable indexable insert: VC.. 1103..
 Minimum pre-drill \varnothing D_{min}: 22 mm

Technical description

Centre offset L ₃	4.6 mm
Minimum pre-drill \varnothing D _{min}	22 mm
Cutting point / joint	16 mm
ISO code toolholder	AH16M SVJCR/L11
Insert size	11 mm
Pack of insert screws	269028 7
suitable indexable insert	VC.. 1103..
Overhang L ₁ recessed holders	30 mm
Neck width	9.5 mm
Overall length L	150 mm
Clamping height L ₂	15 mm
Setting angle κ	142 degrees

Shank Ø D _s	16 mm
Application type	right-hand
Boring depth up to	5×D
Tool material	HSS
Standard	DIN 8024
Through-coolant	yes
Type of product	Boring bar

Accessories

Set of insert screws 10 pieces	269413
Torque screwdriver with scale, to take interchangeable blades maximum torque 500 cNm	659906 500
PrecisionBit for Torx®, shank E 6.3 Torx® profile TX8	674248 TX8
Set of insert screws Type 7	269028 7