

Garant
Boring bar HSS, right-hand, Shank \varnothing / insert size: 20/11 mm

Order data

Order number	261330 20/11
GTIN	4045197653963
Item class	21T

Description

Boring bar HSS 20/11 mm Shank \varnothing D_s: 20 mm
 ISO code toolholder: AH20Q SVJCR/L11
 Cutting point / joint: 20 mm
 Setting angle κ : 142 degrees
 suitable indexable insert: VC.. 1103..
 Minimum pre-drill \varnothing D_{min}: 25 mm

Technical description

Insert size	11 mm
Neck width	11 mm
ISO code toolholder	AH20Q SVJCR/L11
Overhang L ₁ recessed holders	38 mm
suitable indexable insert	VC.. 1103..
Centre offset L ₃	4.6 mm
Minimum pre-drill \varnothing D _{min}	25 mm
Pack of insert screws	269028 7
Cutting point / joint	20 mm
Overall length L	180 mm
Clamping height L ₂	19 mm
Setting angle κ	142 degrees

Shank Ø D _s	20 mm
Application type	right-hand
Boring depth up to	5×D
Tool material	HSS
Standard	DIN 8024
Through-coolant	yes
Type of product	Boring bar

Accessories

Set of insert screws 10 pieces	269413
PrecisionBit for Torx®, shank E 6.3 Torx® profile TX8	674248 TX8
Torque screwdriver with scale, to take interchangeable blades maximum torque 500 cNm	659906 500
Set of insert screws Type 7	269028 7