

Garant
Boring bar HSS, left-hand, Shank Ø / insert size: 20/11 mm

Order data

Order number	261331 20/11
GTIN	4045197653994
Item class	21T

Description

Boring bar HSS 20/11 mm Shank Ø D_s: 20 mm
 ISO code toolholder: AH20Q SVJCR/L11
 Cutting point / joint: 20 mm
 Setting angle κ: 142 degrees
 suitable indexable insert: VC.. 1103..
 Minimum pre-drill Ø D_{min}: 25 mm

Technical description

Insert size	11 mm
Neck width	11 mm
Cutting point / joint	20 mm
suitable indexable insert	VC.. 1103..
Pack of insert screws	269028 7
ISO code toolholder	AH20Q SVJCR/L11
Minimum pre-drill Ø D _{min}	25 mm
Centre offset L ₃	4.6 mm
Overhang L ₁ recessed holders	38 mm
Overall length L	180 mm
Clamping height L ₂	19 mm
Setting angle κ	142 degrees

Shank Ø D _s	20 mm
Application type	left-hand
Boring depth up to	5×D
Tool material	HSS
Standard	DIN 8024
Through-coolant	yes
Type of product	Boring bar

Accessories

Set of insert screws 10 pieces	269413
Torque screwdriver with scale, to take interchangeable blades maximum torque 500 cNm	659906 500
PrecisionBit for Torx®, shank E 6.3 Torx® profile TX8	674248 TX8
Set of insert screws Type 7	269028 7