

Garant
Boring bar HSS, right-hand, Shank \varnothing / insert size: 16/11 mm

Order data

Order number	261334 16/11
GTIN	4045197654014
Item class	21T

Description

Boring bar HSS 16/11 mm Shank $\varnothing D_s$: 16 mm
 ISO code toolholder: AH16Q SVUCR/L11
 Setting angle κ : 93 degrees
 suitable indexable insert: VC.. 1103..
 Minimum pre-drill $\varnothing D_{min}$: 21 mm
 Centre offset L_3 : 11 mm

Technical description

Minimum pre-drill $\varnothing D_{min}$	21 mm
ISO code toolholder	AH16Q SVUCR/L11
Centre offset L_3	11 mm
Pack of insert screws	269028 7
Head length L_1	20 mm
suitable indexable insert	VC.. 1103..
Insert size	11 mm
Overall length L	180 mm
Clamping height L_2	15 mm
Setting angle κ	93 degrees
Shank $\varnothing D_s$	16 mm
Application type	right-hand

Boring depth up to	5×D
Tool material	HSS
Standard	DIN 8024
Through-coolant	yes
Type of product	Boring bar

Accessories

Set of insert screws Type 7	269028 7
Set of insert screws 10 pieces	269413
Torque screwdriver with scale, to take interchangeable blades maximum torque 500 cNm	659906 500
PrecisionBit for Torx®, shank E 6.3 Torx® profile TX8	674248 TX8