

**Garant**
**Boring bar steel, right-hand, Shank  $\varnothing$  / insert size: 12/07 mm**

**Order data**

Order number	261338 12/07
GTIN	4045197941251
Item class	21T

**Description**

Boring bar steel 12/07 mm Shank  $\varnothing D_s$ : 12 mm  
 ISO code toolholder: A12L SVJCR/L07  
 Setting angle  $\kappa$ : 142 degrees  
 suitable indexable insert: VC.. 0702..  
 Minimum pre-drill  $\varnothing D_{min}$ : 13 mm  
 Centre offset  $L_3$ : 2 mm

**Technical description**

Pack of insert screws	269028 27
Overall length L	140 mm
Clamping height $L_2$	11 mm
ISO code toolholder	A12L SVJCR/L07
Head length $L_1$	18 mm
Centre offset $L_3$	2 mm
suitable indexable insert	VC.. 0702..
Neck width $L_4$	7.8 mm
Insert size	7 mm
Minimum pre-drill $\varnothing D_{min}$	13 mm
Setting angle $\kappa$	142 degrees
Shank $\varnothing D_s$	12 mm

Application type	right-hand
Boring depth up to	3×D
Standard	DIN 8024
Through-coolant	yes
Type of product	Boring bar

---

## Accessories

PrecisionBit for Torx®, shank E 6.3 Torx® profile TX6	674248 TX6
Torque screwdriver with scale, to take interchangeable blades maximum torque 200 cNm	659906 200