

Garant
Boring bar steel, right-hand, Shank \varnothing / insert size: 16/11 mm

Order data

| | |
|--------------|---------------|
| Order number | 261338 16/11 |
| GTIN | 4045197654076 |
| Item class | 21T |

Description

Boring bar steel 16/11 mm Shank $\varnothing D_s$: 16 mm
 ISO code toolholder: A16M SVJCR/L11
 Setting angle κ : 142 degrees
 suitable indexable insert: VC.. 1103..
 Minimum pre-drill $\varnothing D_{min}$: 22 mm
 Centre offset L_3 : 2 mm

Technical description

| | |
|---|----------------|
| Head length L_1 | 30 mm |
| ISO code toolholder | A16M SVJCR/L11 |
| suitable indexable insert | VC.. 1103.. |
| Pack of insert screws | 269028 7 |
| Insert size | 11 mm |
| Centre offset L_3 | 2 mm |
| Neck width L_4 | 9.5 mm |
| Minimum pre-drill $\varnothing D_{min}$ | 22 mm |
| Overall length L | 150 mm |
| Clamping height L_2 | 15 mm |
| Setting angle κ | 142 degrees |
| Shank $\varnothing D_s$ | 16 mm |

| | |
|--------------------|------------|
| Application type | right-hand |
| Boring depth up to | 3×D |
| Standard | DIN 8024 |
| Through-coolant | yes |
| Type of product | Boring bar |

Accessories

| | |
|--|------------|
| Set of insert screws 10 pieces | 269413 |
| PrecisionBit for Torx®, shank E 6.3 Torx® profile TX8 | 674248 TX8 |
| Torque screwdriver with scale, to take interchangeable blades maximum torque 500 cNm | 659906 500 |
| Set of insert screws Type 7 | 269028 7 |