

Garant
Boring bar steel, right-hand, Shank Ø / insert size: 20/11 mm

Order data

Order number	261338 20/11
GTIN	4045197654083
Item class	21T

Description

Boring bar steel 20/11 mm Shank Ø D_s: 20 mm
 ISO code toolholder: A20Q SVJCR/L11
 Setting angle κ: 142 degrees
 suitable indexable insert: VC.. 1103..
 Minimum pre-drill Ø D_{min}: 24 mm
 Centre offset L₃: 2 mm

Technical description

suitable indexable insert	VC.. 1103..
ISO code toolholder	A20Q SVJCR/L11
Minimum pre-drill Ø D _{min}	24 mm
Head length L ₁	38 mm
Insert size	11 mm
Centre offset L ₃	2 mm
Pack of insert screws	269028 7
Neck width L ₄	11 mm
Overall length L	180 mm
Clamping height L ₂	19 mm
Setting angle κ	142 degrees
Shank Ø D _s	20 mm

Application type	right-hand
Boring depth up to	3×D
Standard	DIN 8024
Through-coolant	yes
Type of product	Boring bar

Accessories

Set of insert screws Type 7	269028 7
Set of insert screws 10 pieces	269413
PrecisionBit for Torx®, shank E 6.3 Torx® profile TX8	674248 TX8
Torque screwdriver with scale, to take interchangeable blades maximum torque 500 cNm	659906 500