

**Garant**
**Boring bar steel, right-hand, Shank  $\varnothing$  / insert size: 8/05 mm**

**Order data**

Order number	261338 8/05
GTIN	4045197941275
Item class	21T

**Description**

Boring bar steel 8/05 mm Shank  $\varnothing D_s$ : 8 mm  
 ISO code toolholder: A08F SVJCR/L05  
 Setting angle  $\kappa$ : 142 degrees  
 suitable indexable insert: VC.. 0501..  
 Minimum pre-drill  $\varnothing D_{min}$ : 8 mm  
 Centre offset  $L_3$ : 3 mm

**Technical description**

Insert size	5 mm
Centre offset $L_3$	3 mm
ISO code toolholder	A08F SVJCR/L05
Head length $L_1$	15 mm
Overall length $L$	80 mm
Pack of insert screws	269028 26
suitable indexable insert	VC.. 0501..
Minimum pre-drill $\varnothing D_{min}$	8 mm
Clamping height $L_2$	7.5 mm
Neck width $L_4$	6 mm
Setting angle $\kappa$	142 degrees
Shank $\varnothing D_s$	8 mm

Application type	right-hand
Boring depth up to	3×D
Standard	DIN 8024
Through-coolant	yes
Type of product	Boring bar

---

## Accessories

PrecisionBit for Torx®, shank E 6.3 Torx® profile TX5	674248 TX5
Torque screwdriver with scale, to take interchangeable blades maximum torque 200 cNm	659906 200