

Garant
Boring bar steel, left-hand, Shank \varnothing / insert size: 12/07 mm

Order data

Order number	261339 12/07
GTIN	4045197941282
Item class	21T

Description

Boring bar steel 12/07 mm Shank $\varnothing D_s$: 12 mm
 ISO code toolholder: A12L SVJCR/L07
 Setting angle κ : 142 degrees
 suitable indexable insert: VC.. 0702..
 Minimum pre-drill $\varnothing D_{min}$: 13 mm
 Centre offset L_3 : 2 mm

Technical description

Minimum pre-drill $\varnothing D_{min}$	13 mm
ISO code toolholder	A12L SVJCR/L07
Centre offset L_3	2 mm
suitable indexable insert	VC.. 0702..
Setting angle κ	142 degrees
Clamping height L_2	11 mm
Insert size	7 mm
Pack of insert screws	269028 27
Overall length L	140 mm
Neck width L_4	7.8 mm
Head length L_1	18 mm
Shank $\varnothing D_s$	12 mm

Application type	left-hand
Boring depth up to	3×D
Standard	DIN 8024
Through-coolant	yes
Type of product	Boring bar

Accessories

Torque screwdriver with scale, to take interchangeable blades maximum torque 200 cNm	659906 200
PrecisionBit for Torx®, shank E 6.3 Torx® profile TX6	674248 TX6