

**Garant**
**Boring bar steel, left-hand, Shank  $\varnothing$  / insert size: 16/11 mm**

**Order data**

Order number	261339 16/11
GTIN	4045197654106
Item class	21T

**Description**

Boring bar steel 16/11 mm Shank  $\varnothing D_s$ : 16 mm  
 ISO code toolholder: A16M SVJCR/L11  
 Setting angle  $\kappa$ : 142 degrees  
 suitable indexable insert: VC.. 1103..  
 Minimum pre-drill  $\varnothing D_{min}$ : 22 mm  
 Centre offset  $L_3$ : 2 mm

**Technical description**

Pack of insert screws	269028 7
Neck width $L_4$	9.5 mm
Head length $L_1$	30 mm
suitable indexable insert	VC.. 1103..
Insert size	11 mm
Minimum pre-drill $\varnothing D_{min}$	22 mm
ISO code toolholder	A16M SVJCR/L11
Centre offset $L_3$	2 mm
Overall length $L$	150 mm
Clamping height $L_2$	15 mm
Setting angle $\kappa$	142 degrees
Shank $\varnothing D_s$	16 mm

Application type	left-hand
Boring depth up to	3×D
Standard	DIN 8024
Through-coolant	yes
Type of product	Boring bar

---

## Accessories

Set of insert screws 10 pieces	269413
Set of insert screws Type 7	269028 7
PrecisionBit for Torx®, shank E 6.3 Torx® profile TX8	674248 TX8
Torque screwdriver with scale, to take interchangeable blades maximum torque 500 cNm	659906 500