

Garant
Boring bar steel, left-hand, Shank \varnothing / insert size: 8/05 mm

Order data

Order number	261339 8/05
GTIN	4045197941305
Item class	21T

Description

Boring bar steel 8/05 mm Shank $\varnothing D_s$: 8 mm
 ISO code toolholder: A08F SVJCR/L05
 Setting angle κ : 142 degrees
 suitable indexable insert: VC.. 0501..
 Minimum pre-drill $\varnothing D_{min}$: 8 mm
 Centre offset L_3 : 3 mm

Technical description

Clamping height L_2	7.5 mm
Head length L_1	15 mm
suitable indexable insert	VC.. 0501..
Minimum pre-drill $\varnothing D_{min}$	8 mm
ISO code toolholder	A08F SVJCR/L05
Overall length L	80 mm
Centre offset L_3	3 mm
Neck width L_4	6 mm
Setting angle κ	142 degrees
Insert size	5 mm
Pack of insert screws	269028 26
Shank $\varnothing D_s$	8 mm

Application type	left-hand
Boring depth up to	3×D
Standard	DIN 8024
Through-coolant	yes
Type of product	Boring bar

Accessories

Torque screwdriver with scale, to take interchangeable blades maximum torque 200 cNm	659906 200
PrecisionBit for Torx®, shank E 6.3 Torx® profile TX5	674248 TX5